

Data Sheet

LED Area Light Fixture

Model Number:
ZL-ParkL-50K-60W-AM(DM/YM)
ZL-ParkL-50K-120W-AM(DM/YM)
ZL-ParkL-50K-300W-AM(DM/YM)



Adjustable Arm Mount (AM)



Direct Arm Mount (DM)



York Arm Mount (YM)

Parameters

Part Number	ZL-ParkL-50K-60W	ZL-ParkL-50K-120W	ZL-ParkL-50K-300W
Wattage	60W	120W	300W
Dimension	15.9" x 16.5" x 3"	15.9" x 18" x 3"	15.9" x 22.7" x 4.6"
Equal HID Wattage	250W	400W	1000W
Color Temperature	5000K		
Initial Fixture Lumen Output	8000 LM	14000 LM	36000 LM
Weight (lbs)	10 lbs	12 lbs	29 lbs
Input Voltage	120 -277 VAC / 480VAC available		
Efficiency	91%		
Viewing Angles	Type III		
CRI	Greater than 75		
Working Temperature	-20 °C -450°C; 10% - 90% RH		
Storage Temperature	-40 °C - 50 °C		
LED life (L70)	50,000 Hours		
Finish	Brown Color		
Material	Acrylic Diffuser + Aluminum Base		
Protection Rate	IP67, for outdoor use, wet and damp locations		
Safety Rating	UL		
Performance Rating	DLC		
Warranty	5 years		