


Data Sheet

LED Plate Lights

Model Number:

ZL-PlateL-35K(40K/50K)-50W
 ZL-PlateL-35K(40K/50K)-90W
 ZL-PlateL-35K(40K/50K)-120W
 ZL-PlateL-35K(40K/50K)-140W
 ZL-PlateL-35K(40K/50K)-220W



LED Plate Lights

Parameters

| Part Number | ZL-PlateL-50K-50W | ZL-PlateL-50K-90W | ZL-PlateL-50K-120W | ZL-PlateL-50K-140W | ZL-PlateL-50K-220W |
|-------------------|----------------------------------|-------------------|--------------------|--------------------|--------------------|
| Wattage | 50W | 90W | 120W | 140W | 220W |
| Dimension | 7.1" x 7.1"(H) | 9.25" x 11.8"(H) | 9.25" x 11.8"(H) | 10.6" x 11.8"(H) | 13.8" x 11.8"(H) |
| Equal HID Wattage | 175W | 250W | 400W | 600W | 1000W |
| Color Temperature | 3500K, 4000K, 5000K | | | | |
| Lumen Output | 5000 LM | 9000 LM | 12000 LM | 14000 LM | 12000 LM |
| Weight (lbs) | 3 | 6 | 6 | 7 | 11 |
| Base | E26 (Medium Base) | E39 (Mogul Base) | | | |
| Input Voltage | 120 -277 VAC | | | | |
| Light Beam Angles | Flood | | | | |
| CRI | 80 | | | | |
| Working Temp | -4 °F - 113 °F (-20 °C - 45 °C) | | | | |
| Power Factor | 90 | | | | |
| Dimmable | No | | | | |
| Material | Acrylic Diffuser + Aluminum Base | | | | |
| Protection Rate | IP20 | | | | |
| Ratings | ETL | | | | |
| Warranty | 5 years | | | | |

All Rights Reserved